

### USE :

Footwear, leather goods, leather, mattresses, rucksacks, upholstery, nets, filters, binding, technical fabrics, mooring belts and slings, tents and tops.

### POLYESTER THREADS 6.6 HIGH TENACITY

- Great resistance threads.
- Stable to the ultraviolet rays. UVI resistant.
- Melting point > 250°
- Shiny threads, non-hair aspect.
- Acids and putrefaction resistance.
- Water-repellent finish (waterproof) available.

POLIÉSTER ALTA TENACIDAD / POLYESTER HIGH TENACITY			
CÓDIGO	REF.	DESCRIPCIÓN	FORMATO
67803	80/3	42.000 MTS. / 1500 GR.	KING
64803	80/3	28.000 MTS. / 1000 GR.	KING
68803	80/3	21.000 MTS. / 750 GR.	KING
62803	80/3	14.000 MTS. / 500 GR.	KING
64602	60/2	30.000 MTS. / 1000 GR.	KING
68602	60/2	22.000 MTS. / 750 GR.	KING
62602	60/2	15.000 MTS. / 500 GR.	KING
61602	60/2	7.500 MTS. / 250 GR.	KING
67603	60/3	30.000 MTS. / 1500 GR.	KING
64603	60/3	20.000 MTS. / 1000 GR.	KING
68603	60/3	15.000 MTS. / 750 GR.	KING
62603	60/3	10.000 MTS. / 500 GR.	KING
61603	60/3	5.000 MTS. / 250 GR.	KING
64403	40/3	13.000 MTS. / 1000 GR.	KING
68403	40/3	9.750 MTS. / 750 GR.	KING
62403	40/3	6.500 MTS. / 500 GR.	KING
64303	30/3	10.000 MTS. / 1000 GR.	KING
62303	30/3	5.000 MTS. / 500 GR.	KING
61303	30/3	2.500 MTS. / 250 GR.	KING
62203	20/3	3.000 MTS. / 500 GR.	KING
61203	20/3	1.500 MTS. / 250 GR.	KING
67153	15/3	6.900 MTS. / 1500 GR.	KING
64153	15/3	4.600 MTS. / 1000 GR.	KING
68153	15/3	3.450 MTS. / 750 GR.	KING
62153	15/3	2.300 MTS. / 500 GR.	KING
67103	10/3	5.100 MTS. / 1500 GR.	KING
64103	10/3	3.400 MTS. / 1000 GR.	KING
68103	10/3	2.550 MTS. / 750 GR.	KING
62103	10/3	1.700 MTS. / 500 GR.	KING
67093	9/3	4.500 MTS. / 1500 GR.	KING
64093	9/3	3.000 MTS. / 1000 GR.	KING
68093	9/3	2.250 MTS. / 750 GR.	KING
62093	9/3	1.500 MTS. / 500 GR.	KING